

PRIMARY CORNER DESCRIPTION Sec. cor. for 7 & 18 only, W. Bdy.

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6297)

-
- Set a post cor. of secs. 7, 12, 13, and 18, from which
- A Red Fir 48" dia., bears S.25°E., 20 lks. dist.
 - A Yew 6" dia., bears N.47°E., 27 lks. dist.
 - A Yew 6" dia., bears N.25°W., 9 lks. dist.
 - A Yew 24" dia., bears S.20°W., 15 lks. dist.

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6315)

Set new post, witness trees all standing.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13794) and (Vol. 33 Pg. 13876)

-
- The cor. of secs. 7 and 18 only, determined from the remains of the original bearing trees:
- A Yew snag 13" dia., bears N.47°E., 27 lks. dist., no marks remaining.
 - A stump hole bears S.25°E., 20 lks. dist.
 - A stump hole bears S.20°W., 15 lks. dist.
 - A Yew 14" dia., bears N.25°W., 9 lks. dist. no marks remaining on opened blaze. (Byars record dist., 19 lks.)

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 29 S T 29 S
 S 12 $\frac{S}{S}$ $\frac{7}{18}$
 R 4 W R 3 W
 1964

- from which new bearing trees:
- A Fir 12" dia., bears N.34¼°E., 40 lks. dist., mkd. T29S R3W S7 BT.
 - A Fir 7" dia., bears S.61¼°E., 35 lks. dist., mkd. T29S R3W S18 BT.

Cor. Fd. and used in BLM resurvey by Jelley and Rogers, under Contract #997, surveyed Oct. 1979/April 1980 - (DCSO records, Vol. 43 Page 16897)

Fd. ok by D.Edwards, March 1998 - M 128-43