

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 1 only, T29-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13796-97)

Point for the 1/4 sec. cor. of sec. 1 only, on the E. bdy. of T29S R4W at proportionate distance as based on the official plat.

Set an iron post 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd.

T 29 S |
1/4 |
S 1 |
R 4 W |
1964

from which

- A Fir 25" dia., bears S.52°W., 43 lks. dist. mkd. 1/4 S1 BT
- A Fir 12" dia., bears N.36 1/2°W., 44 lks. dist. mkd. 1/4 S1 BT

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, under Group No. 2300: Admin. file #0602, surveyed May/June 2006 - (DCSO recs Vol. 56 Pg 22315 & Plat T29-4 2011-2)

The 1/4 sec. cor. of sec. 1 only, established by Beck in 1964-65, monumented with an iron post, 2 1/2" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by Beck

A sawed fir stump, 32" dia., bears S.48 1/2°W., 26.8 ft. with a healed blaze and fallen trunk lying alongside (Rec. S.52°W., 28.4 ft.)

A fir, 18" dia., bears N.36 1/2°W., 29.0 ft. with a healed blaze.

and new BT

A fir, 7" dia., bears S.64°W., 16 ft., mkd: 1/4 S1 BT.

Each new bearing tree has a 2 1/2"x 1/4" magnetic nail (Mag Nail) driven at the base right side-center.

The geodetic position shown hereon was determined by differentially corrected carrier phase GPS receivers relative to the National Spatial Reference System

Latitude 43°04'29.23"N Longitude 123°07'00.41"W
(NAD 1983 (CORS 96))