

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6311)

Set ¼ sec. post, from which
 A Fir 12" dia., bears S.70°E., 20 lks. dist.
 A Fir 15" dia., bears N.80°E., 25 lks. dist.

Edwin S. Woodford - For: Hall and Potter - April 1953 - C.S. File 42/68 and M 16-21

Set Iron pipe. No trees scribed. Old burn.

Survey by Burton W. Holt - For: Sun Studs, Inc. - July 1979 -M 70-75

Set 1" x 36" I.P. with brass cap mkd. T29S R3W W.M. ¼ S19 S30 1979 PLS 418, from which bears
 A 9" D.Fir S.34½°E., 3.0 ft. mkd. ¼ S30 BT.
 A 11" D.Fir N.29½°E., 19.2 ft. mkd. ¼ S19 BT.
Corner lies on steep North slope in dense under brush, 350 ft. South of South Myrtle County Road.