

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6313)

Set ¼ sec. post, from which
A Fir 48" dia., bears N.50°E., 6 lks.
A Cedar 10" dia., bears S.2°W., 18 lks.

Fd. OK, in GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6348)

Edwin S. Woodford - Wit: M.E. Godfrey; Cliff Potter - April 1953 - C.S. File 42/68-1

Found 10" Cedar S.2°W., 18 lks. set by Hathorn. Tree was down but scribe marks visible. No trace of 48" Fir the NE. was found.

Set iron pipe for corner and mark 2 new trees:
12" Cedar N.23°30'W., 10.3 ft.
10" Cedar S.54°15'W., 17.3 ft.

BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1503, surveyed Sept. 1989/April 1990 - (DCSO records Vol. 50 Page(s) 18957)

The ¼ sec. cor., perpetuated and recorded by Woodford in 1953, monumented with a steel axle 1½" dia., projecting 4" above ground, from which the remains of the original bearing trees:

A rotted and burned Fir root crown, size indeterminate, bears N.50°E., 6 lks. dist., no marks remaining.

A root hole bears S.2°W., 18 lks. dist., with a down Cedar alongside 14" dia., with scribe marks BT visible on an opened blaze.

and bearing trees mkd. by Woodford:

A Cedar 18" dia., bears S.54°W., 27 lks. dist., with healed blaze.

A Cedar 22" dia., bears N.23½°W., 16 lks. dist., with healed blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, directly over the steel axle, with brass cap mkd:

T 29 S R 3 W
¼ S 18
S 19
1989

Deposit a white "DEEP-1" magnetic marker at base of the stainless steel post. (Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner is located 130 lks. E. of Long Wiley Creek, 20 lks. wide, course S.20°W.

Fd. OK, Aug. 1996 by B. Shaner - C.S. File 65/8-6G & M 124-24
Fd. Ok by D. Edwards, 2/2008 - 2008-0031A&B