

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6348)

Set Maple post for the ¼ sec. cor., from which
A Cedar 12" dia., bears S.54°E., 31 lks. dist.
A Fir 36" dia., bears N.30°W., 26 lks. dist.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16896)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 29 S R 3 W
1/4 $\frac{S\ 7}{S\ 18}$
1980

from which
A Fir 7" dia., bears N.51½°E., 32½ lks. dist., mkd. ¼ S7 BT.
A Fir 11" dia., bears S.38½°W., 47 lks. dist., mkd. ¼ S18 BT.

Fd. and used in BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1503, surveyed Sept. 1989/April 1990 - (DCSO records, Vol. 50 Page 18967)