

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6349)

-----  
Set Fir post for ¼ sec. cor., from which  
A Laurel 24" dia., bears N.25°W., 30 lks. dist.  
A Laurel 28" dia., bears S.45°W., 54 lks. dist.

BLM resurvey by James E Jelley and Wayne L Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16900)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 29 S R 3 W  
1/4  $\frac{S}{S} \frac{6}{7}$   
1980

from which  
A Cedar 8" dia., bears N.54½°E., 40 lks. dist., mkd. ¼ S6 BT.  
A Madrone 17" dia., bears S.84°W., 44 lks. dist., mkd. ¼ S7 BT on bark.

Ken Hoffine - For: Lone Rock Timberland Co. - Feb. 2017 - C.S. File 65/95-30

-----  
Found - 1980 BLM brass cap  
New - 14" D.Fir bears S.21°E., 15.9 ft. we scribed T29S R3W ¼ S7 BT and tag tree.  
8" D.Fir bears S.33¾°W., 23.5 ft. we scribed T29S R3W ¼ S7 BT and tag tree.  
17" D.Fir bears N.83¾°W., 27.2 ft. we scribed T29S R3W ¼ S7 BT and tag tree.  
Note - We ran a looped random traverse from the S¼ to the SW sec. cor. of sec. 6, to mark property line. We find the 1980 BLM brass cap on East edge of old skid road, 0.4 ft. above the ground, and put metal U-Post approx. 1.0 ft North of corner.