

PRIMARY CORNER DESCRIPTION Sec Cor for 29, 30, 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6308)

Set post cor. secs. 29, 30, 31 and 32, from which
A Laurel 12" dia., bears S.64°E., 20 lks.
A Fir 6" dia., bears N.65°E., 20 lks.
A Fir 10" dia., bears S.65°W., 38 lks.
A Fir 10" dia., bears N.10°W., 30 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-90

Found - Orig. 10" now 12" rotted stump, shows scribing, S.65°W., 25.1 ft.
Stump hole of NE. BT.
Orig. 10" now 20" Fir, N.10°W., 22.3 ft., not 19.8 ft., shows good scars.
Orig. SE. BT, not found.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 3 W
S 30 | S 29
S 31 | S 32
1962

New BTs- 58" R.Fir bears S.30°W., 34.2 ft. scribed S31 T29S R3W CS BT.
12" Cedar bears S.12°E., 35.9 ft. scribed S32 T29S R3W CS BT.
Rescribe orig. now 20" R.Fir N.10°W., 22.3 ft. S30 T29S R3W CS BT.
12" W.Fir bears N.44°E. 3.4 ft. scribed T29S R3W S29 CS BT.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 4/23/2007 - C.S. File 67/21-30

Found - 2½" dia., brass cap on 1¼" O.D. iron pipe, (properly marked) projects 14" above ground, firmly set.
12" now 14" dia., x 8 ft. tall rotten D.Fir snag, scribing visible in rotted upper blaze, lower blaze healed bears N.49°E., 3.4 ft. (rec. N.44°E., 3.4 ft.) 1962 BT.
12" now 18" dia., I.Cedar, healed double blaze faint, bears S.13½°E., 35.9 ft. (Rec. S.12°E., 35.9 ft.) 1962 BT.
20" now 22" dia., x 4 ft. tall, D.Fir stump, healed double blaze visible bears N.10°W., 22.3 ft. (agrees w/rec) 1962 BT

continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec Cor for 29, 30, 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New - 58" dia., R.Fir, now blown down & out of position
(rec. S.30°W., 34.2 ft.) 1962 BT
6" dia., I.Cedar double blazed & scribed "X" on high
blaze & "CS BT" on low blaze, bears N.84¼°E.,
19.9 ft.
6" dia., P.Pine double blazed & scribed "T29S R3W
S31 CS BT" bears S.45°W., 44.0 ft.
Note - Corner lies on moderately steep east facing slope in
replanted clear cut
Compass decl. 16¼°E.