

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6310)

-----  
Set post cor. secs. 19, 20, 29 and 30, from which  
A Fir 12" dia., bears S.52°W., 37 lks. dist.  
A Fir 12" dia., bears S.74°E., 30 lks. dist.  
A Fir 30" dia., bears N.70°E., 62 lks. dist.  
A Maple 12" dia., bears N.35°W., 16 lks. dist.

Edwin S. Woodfor - Wit: M.E. Godfrey; Cliff Potter - April 1953 - C.S. File 42/68-2

-----  
Found - 30" Fir N.70°E., 62 lks. set by Hathorn in 1857 and still standing with portion of bark scribing still visible. Tree is not 50". Rescribed this tree.  
12" Fir S.74°E., 30 lks., gone but depression in ground still shows that a tree once stood there.  
12" Maple N.35°W., 16 lks. gone but depression in ground and Maple sprouts growing around it.  
No evidence of 12" Fir S.52°W., 37 lks. Ground shows evidence of old slide area.  
Set Iron pipe for corner and mark new trees:  
28" Cedar S.68°15'E., 42.2 ft.  
28" Cedar N.55°W., 51.1 ft.  
40" Fir S.27°45'W., 106.7 ft.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16890-91)

-----  
The Sec. cor., perpetuated and recorded by Woodfor in 1953, monumented with an iron pipe 1" dia., firmly set, projecting 12" above ground, from which the remains of the original bearing trees:

A root hole bears N.70°E., 62 lks. dist., alongside of which is a Fir 30" dia., no marks visible.  
and bearing trees mkd. by Woodford:  
A Cedar 32" dia., bears S.68°W., 68 lks. dist., with scribe marks R3W B visible on partially healed blaze.  
A Fir stump 40" dia., bears S.28°W., 162 lks. dist., with healed blaze.  
A Cedar 30" dia., bears N.55°W., 79 lks. dist., with healed blaze.

At the corner point  
(Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,  
with brass cap mkd:

T 29 S R 3 W  
S 19 | S 20  
S 30 | S 29  
1980

from which new bearing trees:

A Fir 10" dia., bears N.9°E., 46½ lks. dist., mkd. T29S  
R3W S20 BT.

A Fir 10" dia., bears S.33½°W., 121 lks. dist., mkd. T29S  
R3W S30 BT.

Reset iron pipe alongside iron post.

Fd. Ok by R. Brown, 12/20 - 2007 -0017