

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6381)

Set ¼ sec. post, from which
A Laurel 14" dia., bears S.15°W., 60 lks. dist.
A Laurel 18" dia., bears S.45°E., 58 lks. dist.

BLM resurvey, by Boyd W. Peterson, under Group #1394, Surveyed Aug. 1987/Jan. 1988 - (DCSO records Vol. 48 Page(s) 18511-12)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an stainless steel post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:
T 29 S R 4 W
S 19 | S 20
1987

from which
A Fir 7" dia., bears N.59°E., 48½ lks. dist. mkd. ¼ S20 BT
A Fir 5" dia., bears S.68°W., 18 lks. dist. mkd. ¼ S19 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

All found OK as per USBLM record by B. Shaner, Feb. 1997 - M 124-43 and C.S. File 65/13-2F
Fd. BC 3/2017 - M173-26 by R. Brown

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024

Found ok per record. Added paint, snow blaze, nails, and LS washer 90216 at left side center of BTs and new tag to a 10" Fir.