

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6312)

Marked a Sugar Pine 12" dia., for cor. secs. 17, 18, 19 and 20, from which

- A Fir 24" dia., bears S.30°W., 31 lks. dist.
- A Fir 18" dia., bears N.80°W., 19 lks. dist.
- A Fir 6" dia., bears N.50°E., 26 lks. dist.
- A Fir 20" dia., bears S.70°E., 28 lks. dist.

Fd. and used in GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6347)

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson and Ward - June 26-27, 1920 - Vol. 4 Pg. 8; M 8-1 and C.S. File 37/24

Corner is a tree now fire killed and leaning against an adjoining tree. Three O.B.T.s alive and standing except scribe marks obliterated or partially so by fire. Fourth BT is cut. The stump is in place and sound.

Set for corner, a Yew wood post 6" x 6" x 48", scribed T29S S17 on NE. face; R3W S20 on SE. face; S19 on SW. face; and S18 CS on NW. face.

Reblazed and scribed original BTs where in good condition.

- 28" Fir S.30°W., 31 lks. (OBT) "T29S R3W S19 CS BT"
- 24" Fir S.70°E., 31 lks. (OBT) "T29S R3W S20 CS BT"
- 30" Sugar Pine N.27°W., 61 lks. "T29S R3W S18 CS BT"
- 20" Cedar N.75°E., 55 lks. "T29S R5W S17 CS BT"

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Wm. Stoffel, crew - Oct. 1962 - C.S. File 52/126-70

Found all BTs as recorded by B.B.I.

Sugar Pine N.17°W., not N.27°W., 40.3 ft., shows good scar SE. BT, down.

SW. and NE. BTs OK, show good bark scribing.

Also find 6"x6" scribed stake on ground at corner and 1½" Iron pipe.

Irving's BTs check for dist. OK, as measured to faces.

Set Brass cap at cor. mkd: County Surveyors Office

T	29	S	R	3	W
	S	18		S	17
	S	19		S	20
				1962	

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

New BTs- 24" Cedar bears N.26°W., 12.5 ft. scribed S18 T29S R3W CS BT.
10" R.Fir bears S.2°E., 57.4 ft. scribed S20 T29S R3W CS BT.

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16892)

BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1503, surveyed Sept. 1989/April 1990 - (DCSO records Vol. 50 Page(s) 18955-56)

(Corner Report)
The Sec. Cor., monumented with an iron post 1¼" dia., firmly set, projecting 14" above ground, with brass cap mkd. in 1962 from which the remains of the original bearing trees:
A root hole bears N.50°E., 26 lks. dist., with a down Fir alongside 18" dia., no visible marks.
A root hole bears S.70°E., 28 lks. dist., with a down Fir alongside 36" dia., with healed blaze.
A Fir 32" dia., bears S.30°W., 34 lks. dist., with healed blaze.
A Fir root crown bears N.80°W., 19 lks. dist., no visible marks.
and the remains of bearing trees mkd. by Irving in 1930:
A Cedar 31" dia., bears N.75°E., 57 lks. dist., bark scribed S17 T29S R3W CS BT. (Rec. N.71°E., 55 lks.)
A Sugar Pine snag 40" dia., bears N.18°W., 63 lks. dist., with rotted blaze.
and bearing trees mkd. by Byron in 1962:
A Fir 17" dia., bears S.3°E., 87 lks. dist., with a healed blaze.
A Cedar 30" dia., bears N.26°W., 18½ lks. dist., with healed blaze. (Rec. N.30°W.)
Corner is located at the corner of barbed wire fences, extending irregularly S. and W.