

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6349)

Set Laurel post for ¼ sec. cor., from which
A Laurel 14" dia., bears S.80°E., 9 lks. dist.
A Laurel 12" dia., bears N.75°W., (lks. omitted)

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16897-98)

The ¼ sec. cor., determined at record bearing and distance from the remains of the original bearing trees:

A Madrone 26" dia., bears S.80°E., 9 lks. dist., with chaining notch and axe marks visible on decayed blaze.
A root hole bears N.75°W., 78 lks. dist.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S R 3 W
1/4
S 7 S 8
1980

from which new bearing trees:

A Fir 6" dia., bears S.4°E., 27½ lks. dist., mkd. ¼ S8 BT
A Fir 7" dia., bears N.42 3/4°W., 44 lks. dist., mkd. ¼ S7 BT.