

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6349)

- 
- Set Fir post for the cor. to secs. 5, 6, 7 and 8, from which
    - A Fir 10" dia., bears N.74°E., 46 lks. dist.
    - A Fir 40" dia., bears S.87°E., 28 lks. dist.
    - A Laurel 18" dia., bears S.30°W., 18 lks. dist.
    - A Laurel 12" dia., bears N.25°W., 44 lks. dist.

Douglas County Surveyors Office - Karen Reed; F.C. Silagy and Wit: Burt Holt, Sun Studs, Inc. - July 16, 1979 - C.S. File 60/34-3

- 
- Found - 36" Fir, orig. 40", bears S.87°E., 18.5 ft. with partial bark scribe "S" visible.
    - An 18" Laurel found fallen and rotted, bears S.30°W., 11.0 ft. (Orig.)
  - Set a 1" x 36" I.Pipe with brass cap marked "Douglas County Surveyor T29S S6 S5 S7 S8 R3W 1979".
  - New BTs- 5" Fir scribed "T29S R3W S6 CS BT" in double blaze, bears N.24°W., 24.5 ft.
  - 17" Cedar scribed "T29S R3W S8 CS BT" in double blaze, bears S.46½°E., 8.2 ft. with double blaze.
  - 7" Fir scribed "T29S R3W S6 CS BT" in double blaze bears N.75°W., 15.2 ft.
  - 8" W.Fir scribed "T29S R3W S5 CS BT" in a double blaze, bears N.87°E., 44.5 ft.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16898-99)

- 
- The Sec. cor., perpetuated and recorded by Reed in 1979, monumented with an iron post 1¼" dia., firmly set, projecting 6" above ground, with brass cap mkd. in 1979, from which the remains of an original bearing tree:
- A Fir snag 40" dia., bears S.87°E., 28 lks. dist., with illegible scribe marks visible on bark.
- and bearing trees mkd. by Reed:
- A Fir 8" dia., bears N.72°E., 67 lks. dist., with scribe marks T29S R3W S5 CS BT visible on open double blaze.
  - A Cedar 18" dia., bears S.46¼°E., 12 lks. dist., with scribe marks T29S R3W S8 CS BT.
  - A Fir 8" dia., bears N.75°W., 23 lks. dist., with scribe marks T29S R3W S6 CS BT visible on open double blaze.
- (Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 5" dia., bears N.24°W., 37 lks. dist., with scribe marks T29S R3W S6 CS BT visible on open double blaze. and a new bearing tree:  
A Fir 6" dia., bears S.13½°W., 32 lks. dist., mkd. T29S R3W S7 BT.