

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6350)

Set an Alder post for ¼ sec. cor., from which
A Hemlock 16" dia., bears S.25°E., 39 lks. dist.
A Fir 50" dia., bears N.35°W., 17 lks. dist.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16901-02)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:
T 29 S R 3 W
1/4
S 6 | S 5
1980

from which
A Cedar 4" dia., bears S.60 ¾°E., 9½ lks., mkd. X BT.
A Fir 9" dia., bears S.89½°W., 25 lks., mkd. ¼ S6 BT.

Fd BC & 1 BT by David Edwards 5/2006 - M 150-50