

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, N. Bdy.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Pages 6327)

Set Fir post for cor. to secs. 5, 6, 31 and 32, from which
A Laurel 12" dia., bears N.22°E., 105 lks.
A Laurel 13" dia., bears S.45°E., 21 lks.
A Laurel 18" dia., bears S.52°W., 25 lks.
A Fir 10" dia., bears N.70°W., 7 lks.

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5562)

Cor. secs. 5, 6, 31 and 32, which is a stake marked and witnessed as described by the surveyor general.
I destroy markings on this cor. and bearing trees referring to secs. 31 and 32.

Survey by Burton W. Holt - For: Sun Studs - April 19, 1976 - M 59-77

Set 1½" x 34" Iron pipe with brass cap, from which
A 6" Madrone bears S.53°W., 26.5 ft. mkd. T29S R3W S6 BT
A 6" Cedar bears S.70 ¾°E., 37.3 ft. mkd. T29S R3W S5 BT

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16877)

The Sec. cor., reestablished by proportionate measurement and recorded by Holt in 1976, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1½" dia., firmly set, projecting 6" above ground, with brass cap mkd.

T 28 S R 3 W
S 31

S 6 | S 5
T 29 S R 3 W
418 1976

from which bearing trees mkd. by Holt
A Cedar 6" dia., bears S.70 ¾°E., 56 lks. dist., with scribe marks T29S R3W S5 BT visible on open blaze.
A Madrone 6" dia., bears S.47¼°W., 40 lks. dist., with scribe marks T29S R3W S6 BT visible on bark.
Cor. is located on top of a spur, slopes S.20°E., and in SW. cor. of a logged area, edge bears N. and S.60°E.

continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, N. Bdy.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: White Family Investments LLC - 5/2006 - M 150-50

Found - Brass cap by Holt in 1976
10" Cedar S.70¾°E., 37.0' healed blaze.
8" Dead Madrone S.47¼°W., 26.4'

New BT - 5" Cedar S.37°W., 20.8', scribed T29S R3W S6 BT"

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024 - M185-29 A/D

Found - Brass cap on 1½" I.P. 0.5" above ground.
14" Cedar bears S.70¾°E. 37.3' with healed blaze and tag.
8" Cedar bears S.37¼°W. 20.8' with healed blaze and tag.