

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCS0 records Vol. 15 Page(s) 6309)

Set ¼ sec. post, from which
A Fir 10" dia., bears S.5°E., 5 lks. dist.
A Laurel 12" dia., bears N.88°W., 18 lks. dist.

Survey by Glenn S. Baughman - For: John Westheimer - Aug. 1977 - M 65-42

Set Brass cap, from which
A 10" Cedar bears S.32°W., 11.4 ft. scribed ¼ S32 BT.
A 12" D.Fir bears N.62°E., 14.6 ft. scribed ¼ S29 BT.

Fd. OK, Oct. 1992 by G. Lang - M 117-2

David Edwards - Crew: Brant Miller & Eric Sprinkle - 2/12/2024 - C.S. File 65/113-32

Found - Brass capped iron pipe per M65-42
A 17" dia., Cedar with healed blaze, bears S.32°W., 11.4'.
A 14" dia., Fir stump bears N.62°E., 14.6'
New - A 10" Cedar scribed "¼ S29 BT" bears N.14°E., 12.9'
5/5' steel posts are set 2' east & 2' south on line.
Note - Dec. 15°E.