

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 240440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1503, Surveyed Sept. 1989/April 1990 - (DCSO records Vol. 50 Page(s) 18961)

Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line.
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground with brass cap mkd. T 29 S R 3 W
C¼
S 17
1989

from which
A Cedar 16" dia., bears S.26°E., 12 lks. dist., mkd. C¼ S17 BT.
A Fir 7" dia., bears N.48°W., 17½ lks. dist., mkd. C¼ S17 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024 - M185-29 A/D

Found - 3¼" BLM brass cap on a 2½" I.P. 0.5' above ground.
23" Cedar bears S.26½°E. (S.26°E.) 7.6' (12 lks) to a nail left side center with healed blaze and illegible tag.
16" Fir bears N.55¾°W. (N.48°W.) 11.5' to a nail right side center with a healed blaze.
New - Added nail to both BTs.