TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6314)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.6°E., 287 lks.
A Fir 24" dia., bears S.80°W., 351 lks.

Fd. and used in GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6347)

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors,under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16895)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 29 S R 3 W

1/4 S 8 / S 17
1979

from which
A Fir 4" dia., bears N.6°W., 18½ lks. dist., mkd. X BT.
A Fir 7" dia., bears S.12 3/4°W., 41 lks. dist., mkd. ¼ S17 BT.

From this point, a point established by person(s) unknown, monumented with an iron pipe, firmly set, projecting 12" above ground, bears S.4 3/4°W., 0.315 chs. dist.

Fd. and used in BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1503, surveyed Sept. 1989/April 1990 -(DCSO records Vol. 50 Page(s) 18961-62)

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024 - M185-29 A/D

Found ok per record. Added paint, snow blaze, nails at right side center of BTs, and LS washer 90216, and new tag to the 14" Fir.