

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6349)

Set Fir post for ¼ sec. cor., from which
A Fir 70" dia., bears S.40°E., 27 lks. dist.
A Fir 14" dia., bears N.70°W., 18 lks. dist.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16899)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:
T 29 S R 3 W
1/4 $\frac{S \ 5}{S \ 8}$
 1980

from which
A Fir 8" dia., bears N.13¼°E., 88 lks. dist., mkd. ¼ S5 BT
A Fir 9" dia., bears S.24½°E., 28 lks. dist., mkd. ¼ S8 BT

David Edwards - For: White Family Investments LLC - 5/2006 - M 150-50

Found - Brass cap
 11" Fir N.13¼°E., 58.1', healed blaze.
Set - 6' steel post 2' north
New BT - 16" Cedar S.84°E., 27.3', scribed "T29S R3W S8 BT"