

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6326)

Set Laurel post for ¼ sec. cor., from which
A Laurel 6" dia., bears N.45°E., 15 lks.
A Fir 6" dia., bears S.40°W., 5 lks.

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5562)

¼ sec. cor. which is a stake greatly decayed, marked as described by the surveyor general. Bearing trees have been destroyed.
Set Fir stake 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., marked ¼ S. on N. and S5 on S. face, and dig pits, 18 x 18 x 12 ins., E. and W. of cor., and raise mound of earth, 3½ ft. base, 1½ ft. high S. of cor., from which
A Fir 8" dia., bears S.10°W., 9 lks. dist. mkd. ¼ S5 BT.
No other tree fit to mark.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Mike Stone, crew - July 20, 1962 - C.S. File 52/126-9

Found orig. 8" now 10" Fir, S.10°W., 5.9 ft. previously opened, shows good scribing.
Set Brass cap at cor. mkd: County Surveyors Office
N ¼ S5 T29S R3W
1962
New BT - 8" R.Fir bears S.88°W., 16.3 ft. scribed N ¼ S5 CS BT. (Dist to BT measured to base, tree leans to West)

Cor. Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16876)

Fd BC & 2 BTs by David Edwards 5/2006 - M 150-50