

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6300)

Set Post cor. secs. 32, 22, 4 and 5, from which
A Fir 18" dia., bears S.68°E., 126 lks.
A Fir 24" dia., bears S.8°W., 108 lks.
An Ash 12" dia., bears N.75°E., 250 lks.
An Alder 18" dia., bears N.3/4°W., 713 lks.

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6318)

At sec. cor., Set post as per instructions.
Witness trees all standing.

C.W. Springer, Deputy Co. Surveyor - Wit: N.E. Richardson; Thomas Hatfield - Oct. 20, 1923 - "Old" corner book, Pg. 120 and see C.S. File 6/29; Vol. 3 Pg. 169

Reestablished from stump of only remaining BT called for as 24" Fir S.8°W., 108 lks.
Drove an Iron pipe 3/4" x 24" in ground and marked:
A 12" B.Oak S.60°15'W., 168.9 ft.
A 10" Ash S.52°45'E., 178.0 ft.
A 10" Alder N.42°10'E., 17.7 ft.
A 6" Ash N.7°50'W., 210.7 ft.

Survey by John H. Markham, Jr. - Wit: E.C. Tracy and W.E. Markham - Feb. 6, 1952 - C.S. File 40/386-10

I found all four BTs but no Iron pipe at corner.
I Set 3/4" x 30" Iron pipe, from which
A 12" Ash bears S.12°E., 48.5 ft. mkd. S4 T30S R3W BT.
Days Creek bears South 140.0 ft.
There are fences bearing North and South and S.64°W. from corner point.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14035)

The Sec. cor., perpetuated and recorded by Springer in 1923, from the remaining original bearing tree which is no longer in existence, monumented with an iron bolt, 24" long, 3/4" dia., the top 2" below the surface of the ground, from which bearing trees mkd. by Springer:
(Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T30-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An Alder snag 13" dia., bears N.43°E., 27 lks. dist., with no marks remaining.

A B.Oak 18" dia., bears S.58½°W., 256 lks. dist., with a healed blaze.

An Ash 29" dia., bears N.9½°W., 320 lks. dist., with a healed blaze.

and a bearing tree mkd. by Markham in 1952:

An Ash 16" dia., bears S.14½°E., 74 lks. dist., with scribe marks S4 T30S R3W BT visible on partially healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, over the iron bolt, with brass cap mkd:

T 29	S R 3 W
S 32	S 33
S 5	S 4
T 30	S
1967	

from which a new bearing tree:

An Ash 17" dia., bears N.2°E., 150 lks. dist. mkd. T29S R3W S33 BT.

The corner is located at the corner of wire fences which extend S.3°E., S65°W. and N.3°W.

Fd. OK, Oct. 1993 by M. Hull - M 118-4

Fd. Ok by Tony Hostetter 6/2006 - M151-9