TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6301)

Set ¼ sec. post, from which
An Oak 8" dia., bears N.62°E., 14 lks. dist.
A Pine 30" dia., bears S.10°W., 58 lks. dist.

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6339)

Witness trees standing. Set new post from same, from which
An Oak 8" dia., bears N.62°E., 14 lks. dist.
A Pine 30" dia., bears S.10°W., 58 lks. dist.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14040)

The ¼ sec. cor. of secs. 32 and 33, restored by the method of broken boundaries; there is no remaining evidence of the original corner.
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd. ¼
S32|S33
T 29 S R 3 W
1967
from which
A Fir 17" dia., bears N.25¼°E., 56 lks. dist. mkd. ¼ S33 BT.
A Fir 20" dia., bears N.11¼°W., 74½ lks. dist. mkd. ¼ S32 BT.
An iron pipe 2" dia., firmly set, extending 2" above ground, bears North, 1.27 chs. dist.

Fd. OK, Oct. 1993 by M. Hull - M 118-4

Found ok by David Edwards - 6/2025 - 2025-0020 A/B