

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6301)

Set post cor. secs. 28, 29, 32 and 33, from which
A Fir 24" dia., bears N.60°W., 13 lks. dist.
A Fir 18" dia., bears S.40°W., 41 lks. dist.
A Fir 30" dia., bears S.20°E., 43 lks. dist.
A Laurel 18" dia., bears N.15°E., 88 lks. dist.

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6340)

Set new post, witness trees all standing. (As listed above)

Ben B. Irving, County Surveyor - N.E. Richardson; Loren Weber
May 31, 1941 - C.S. File 16/55

Location identified from original BT,
A Fir 24" which bears N.60°W., 13 lks. which has fallen down, scribe marks visible.
A Fir snag completely burned, S.30°E., 43 lks.
A Laurel 42" dia., N.15E., 88 lks., alive and in excellent shape which I did not chop out but marked with an X.
Set a Cedar post 4" x 6" x 48", 15" in the ground for the corner and blazed and scribed new bearing trees as follows:
A Fir 26" dia., which bears N.22°W., 39 lks.
A Fir 12" dia., which bears S.21°E., 90 lks.
A Cedar 42" dia., which bears S.59°W., 26 lks.
A Cedar 12" dia., which bears N.29°E., 76 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Wm. Stoffel, crew - Oct. 1962 - C.S. File 52/126-69

Found 4" x 4" squared and scribed post at corner and all BTs as recorded by Irving in 1941.
Cedar to SW., now stump, scribed.
Fir to SE., down.
Fir to NW., down.
Cedar to NE., dead.

Set brass cap alongside cor. post, mkd:
County Surveyors Office
T 29 S R 3 W
S 29 | S 28
S 32 | S 33
1962

New BTs- 23" Cedar bears S.26°E., 27.2 ft. scribed S33 T29S R3W CS BT. (Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" Fir bears N.81°W., 42.1 ft. scribed S29 CS BT.
16" R.Fir bears N.42°E., 67.7 ft. scribed S28 T29S
R3W CS BT.
No trees near to SW.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral
Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 -
(DCSO records Vol. 34 Page(s) 14040-41)

(Corner Report)
The sec. cor. perpetuated and recorded by Irving in 1941,
again perpetuated and recorded by Byron in 1962, monumented
with an iron post, 1" dia., firmly set, extending 14" above
ground with 1962 brass cap,
from which the remaining original bearing trees
The stump hole of an uprooted Madrone 32" dia., bears
N.13½°E., 88 lks. dist., with a healed original blaze
and mkd. with an X at breast height by Irving in 1941.
(Rec. N.15°E.)
A Fir root crown, size indeterminate, bears S.20°E., 43
lks. dist., with no marks remaining.
The stump hole of an uprooted Fir 28" dia., bears N.60°W.,
13 lks. dist., with no marks remaining.
and bearing rees mkd. by Irving in 1941
A Cedar snag 15" dia., bears N.35°E., 78 lks. dist., with
scribe marks T29S R3W S28 BT visible on partially
healed double blaze.
The stump hole of an uprooted Fir 15" dia., bears S.21°E.,
90 lks. dist., with a healed blaze.
A sawed Cedar stump 35" dia., bears S.63½°W., 26 lks.
dist. bark scribed T29S R3W S32 BT.
The stump hole of an uprooted Fir 26" dia., bears N.17°W.,
39 lks. dist., bark scribed T29S R3W S29 CS BT.
and bearing trees mkd. by Byron in 1962
A Fir 16" dia., bears N.40¼°E., 103 lks. dist. with a
pitched over blaze.
A Cedar 26" dia., bears S.29 3/4°E., 42 lks. dist. with
scribe marks T29S R3W S33 CS BT visible on partially
healed double blaze.
A W.Fir 10" dia., bears N.82¼°W., 63½ lks. dist. with a
healed double blaze.

Found ok by David Edwards - 6/2025 - 2025-0020 A/B

2