

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6308)

Marked a Laurel 3" dia., for 1/4 sec. cor., from which
A Laurel 12" dia., bears N.15°E., 24 lks.
A Sugar Pine 40" dia., bears S.72°W., 57 lks.

Cor. Fd. and used in GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6345)

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14045)

The 1/4 sec. cor., monumented with the root crown and sprout of the original corner tree, now a Madrone 7" dia., from which the original bearing trees:

The stump hole of a Madrone bears N.15°E., 24 lks.
A sawed Pine stump 50" dia., bears S.72°W., 60 lks., with scribe marks BT visible on opened blaze. (Rec. dist. 57 lks., dist. to face, 57 lks.)

from which new bearing trees and a reference monument:
A Cedar 12" dia., bears N.70°E., 56 1/2 lks., mkd. 1/4 S9 BT.
A Fir 12" dia., bears N.38°W., 84 lks., mkd. 1/4 S8 BT
An Iron post 28" long, 2 1/2" dia., set 22" in the ground for a reference monument, bears South, 2 1/2 lks., with brass cap mkd. RM T29S R3W 1/4 S 8/S9 1966 and an arrow pointing to the corner.

Corner is located on a ridge, bears N.20°W. and S.20°E.

Fd. OK by L.Roberts, May 1999 - M131-64
Fd. OK by R. Brown, July 2003 - M142-63

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2654, surveyed Oct./Nov. 2012 - (DCSO records Vol. 58 Page(s) 23030)

Point for the 1/4 sec. cor. of secs. 8 and 9, falls in a roothole where it is impracticable to set a permanent monument, determined at record bearing and dist. from a reference monument established by Jelley and Roseberry in 1966-67

An iron post, 2 1/2" dia., firmly set, projecting 7" above ground, bears South, 1.65 ft., with brass cap mkd. RM T29S R3W 1/4 S8 S9 1966, and an arrow pointing toward the cor.

continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of the original bearing trees
A roothole bears N.15°E., 15.8 ft., with madrone snag, 11" dia., lying alongside, with a partially healed blaze.
A sawed, decayed pine stump, 48" dia., bears S.72°W., 39.6 ft., with scribe marks BT visible on an open blaze.
and bearing trees mkd. by Jelly and Roseberry
A cedar, 21" dia., bears N.70°E., 37.3 ft., with a healed blaze.
A fir, 21" dia., bears N.38°W., 55.4 ft., with a healed blaze.

NAD 83 (2011)

Latitude: 43°03'52.49"N. Longitude: 123°04'45.30"W.