

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page 6346)</p> <p>-----</p> <p>Set Fir post for ¼ sec. cor., from which A Maple 8" dia., bears S.88°E., 27 lks. dist. A Maple 8" dia., bears S.60°W., 34 lks. dist.</p>
<p>BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16888)</p> <p>-----</p> <p>Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 29 S R 3 W 1/4 S 5*S 4 1980</p> <p>from which A Yew 10" dia., bears S.68°E., 26 lks. dist. mkd. ¼ S4 BT A Fir 6" dia., bears S.47°W., 27½ lks. dist. mkd. ¼ S5 BT</p>
<p>Rob Ward - For: Seneca Jones Timber Co. - Jan. 2003 - M141-30</p> <p>-----</p> <p>Found - 3" BLM brass cap dated 1981 12" Yew bears S.68°E., 17.2' - healed face Rec. 6" Fir S.74°W now a rotted stub</p> <p>New - 8" D.Fir bears N.83°W., 13.5' blazed, scribed "¼ S5 BT"</p>
<p>Fd BC & 2 BTs by David Edwards 5/2006 - M 150-50</p>
<p>BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2654, surveyed Oct./Nov. 2012 - (DCSO records Vol. 58 Page(s) 23031)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 4 & 5, perpetuated by Rice, in 2003, monumented with an iron post, 2½" dia. firmly set, projecting 8" above ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Jelley and Rogers in 1979-80 A yew, 12" dia., bears S.68°E., 17.2 ft., with fragmentary scribe marks visible on a partially healed double blaze. A decayed fir stump, 8" dia., bears S.47°W., 18.2 ft., with no marks visible. and a bearing tree mkd. by Rice</p> <p style="text-align: center;">continued next page</p>

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 12" dia., bears N.83¼°W., 13.4 ft., with a healed double blaze.
Corner is located 86 ft. N. of a ravine, drains N.80°E.
NAD 1983 (2011)
Latitude: 43°04'43.26"N. Longitude: 123°04'43.91"W.