

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, N. bdy.

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6326)

-----  
Set Laurel post for cor. to secs. 4, 5, 32 and 33, from which  
A Fir 14" dia., bears N.20°E., 22 lks.  
A Fir 46" dia., bears S.50°E., 37 lks.  
A Fir 44" dia., bears S.70°W., 33 lks.  
A Fir 18" dia., bears N.30°W., 16 lks.

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5562)

-----  
Cor. secs. 4, 5, 32 and 33, which is a stake marked and witnessed as described by the surveyor general.  
I destroy markings on stake and bearing trees referring to secs. 32 and 33.

Survey by Warren D. Hootman - For: Mr. J.P. Heath - Sept. 21, 1960 (Filed Jan. 13, 1961) - C.S. File 51/164 and M 20-5

-----  
Find two Firs of approx. size which match for bearing and distance which I believe to be the original BTs.  
I set a 3/4" Iron pipe from the 2 BTs at the distance and bearing called for by the government notes and witness the corner as follows:  
Madrone 4" DBH bears West 5.2 ft.  
Madrone 16" DBH bears S.45°E., 13.5 ft.

Survey by Bruce A. Shaner, LS #430 - For; Longview Fibre - Sept. 25, 1978 - M 73-52

-----  
Found 3/4" Iron pipe.  
I Set a brass cap alongside mkd. "5, 4, T29S R3W 1978", from which  
16" now 20" Madrone BT scribes visible bears S.45°E., 13.5 ft.  
10" D.Fir, I scribe "T29S R3W S5 BT" bears S.33°W., 54.4 ft.  
46" D.Fir, Orig. BT, snag, face chopped out, bears S.50°E., 24.4 ft.  
44" D.Fir, Orig. BT, blowdown, bears S.70°W., 21.8 ft.  
36" D.Fir, Orig. BT, blowdown, bears N.20°E., 14.5 ft.  
4" Madrone BT, bears West, 5.2 ft.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, N. Bdy.

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16875)

-----  
The Sec. cor., perpetuated and recorded by Hootman in 1960, further perpetuated and recorded by Shaner in 1978, monumented with an iron post 1¼" dia., firmly set, projecting 3" above ground with brass cap mkd. by Shaner, from which the remains of the original bearing trees:

A Fir stump 38" dia., bears S.50°E., 37 lks. dist., no marks visible on opened blaze.

and bearing trees mkd. by Hootman:

A Madrone stump 17" dia., bears S.48°E., 21 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A Madrone 4" dia., bears N.76¼°W., 7 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and new bearing trees:

A Fir 4" dia., bears S.35°E., 119 lks. dist. mkd. X BT.

A Fir 9" dia., bears S.46°W., 157 lks. dist., mkd. T29S R3W S5 BT.

Rob Ward - For: Seneca Jones Timber Co. - Jan. 2003 - M141-30

-----  
Found - BLM brass cap dated 1981  
38"x' D.Fir stump bears S.50°E. 24,4', burned face  
17"x5' Madrone stump with metal cap bears S.48°E., 13.9' -partially healed face.  
10"x5' D.Fir stump with metal top bears S.46°W., 103.6' - healed face

Rec. 4" madrone N.76¼°W., now stump sprout no marks.

Rec. 4' D.Fir S.35¼°E., now burned stub

New - 8" D.Fir bears S.70¼°W 9.51 blazed, scribed "T29S R3W S5 BT"

6" D.Fir bears S.36½°E., 4.7' blazed, scribed "T29S R3W S4 BT"

Also found 3/4" iron pipe next to brass cap.