

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6319)

-----  
Set Maple post for ¼ sec. cor., from which  
Ash tree, 6" dia., bears N.25°E., 19 lks.  
Alder tree, 24" dia., bears S.20°E., 21 lks.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14033)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 29 S R 3 W  
¼ S 33  
1967

from which  
A Fir 16" dia., bears N.9½°E., 151 lks. dist., mkd. ¼ S33 BT.  
A Fir 6" dia., bears N.33½°W., 111 lks. dist. mkd. ¼ S33 BT.