

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6305)

Set ¼ sec. post, from which
A Fir 50" dia., bears S.77°E., 35 lks.
A Pine 18" dia., bears N.58°E., 115 lks

Douglas County Surveyors Office - John Powell and crew - June 30, 1966 - C.S. File 52/126-146

Found - 50" D.Fir now snag, S.77°E., 23.1 ft., faint bark scribe "¼S". Opened BT scar for old burnt face. No legible scribing.
18" Pine N.58°E., 75.9 ft., now hole in ground, good bearing and distance. Pine down the hill about 50.0 ft.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 3 W
¼ $\frac{S}{S} \frac{21}{28}$
1966

New BTs- 9" Laurel N.39°E., 7.0 ft. mkd. ¼ S21 CS BT.
6" Cedar S.8°W., 9.8 ft. mkd. ¼ S28 CS BT.
This corner lies East of creek 325 ft. Yellow tag on W.Fir at end of cat trail, 137 ft. East of corner.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16881)

The ¼ sec. cor., perpetuated and recorded by Powell in 1966, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1966, from which the remains of the original bearing trees
A decayed Fir snag 50" dia., bears S.77°E., 37 lks. dist., no marks visible. (Rec. 35 lks.)
and bearing trees mkd. by Powell
A Madrone 10" dia., bears N.39°E., 10½ lks. dist., with scribe marks S21 visible on partially healed blaze.
A Cedar 9" dia., bears S.8°W., 15 lks. dist., with scribe marks S28 CS visible on partially healed blaze.
and a new bearing tree
A Fir 8" dia., bears N.1°E., 33 lks. dist., mkd. ¼ S21 BT.

FD. BC & 3 BTs - by D. Edwards, 1/2007 - M152-14