

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 340540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14048-49)

Point for the center ¼ sec. cor. of sec. 9, at intersection with the E. and W. center line.
Set a fiberglass post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 29 S R 3 W
C¼ S 9
1966

from which
A Fir 12" dia., bears N.75°E., 39½ lks. dist., mkd. C¼ S9 BT.
A Cedar 16" dia., bears S.63°W., 112 lks. dist., mkd. C¼ S9 BT.

Fd. OK by R. Brown, July 2003 - M142-63

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2154, Surveyed April/May 2007 - DCSO records Vol. 57 Page(s) 22576

The center ¼ sec. cor. of sec. 9, monumented with a fiberglass post, 2½" dia., firmly set, projecting 3" above the ground, with brass cap (properly) mkd.
from which BTs mkd. by Jelley and Roseberry in 1966-67
A fir, 27" dia., bears N.75°E., 26.1 ft., with a healed blaze.
A cedar, 53" dia., bears S.63°W., 73.9 ft., with a healed blaze.

Fd OK 10/17/2018 by DCSO C.S. File 67/45-25
NAD 83 N 519989.208 E 4234798.267
Lat: 43°03'52.473" Long: 123°04'09.672'