TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6346)

Set Dogwood post for the ¼ sec. cor., from which
A Fir 12" dia., bears S.20°E., 11 lks. dist.
A Cedar 20" dia., bears N.15°E., 40 lks. dist.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14047)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd: T 29 S R 3 W

¼ S 4 / S 9

1966

from which
A Fir 8" dia., bears N.57°E., 34½ lks. dist., mkd. ¼ S4 BT.
A Fir 8" dia., bears S.59°E., 39 lks. dist., mkd. ¼ S9 BT.

Found OK Jan. 2003 by R. Rice, - M141-50
Fd. OK by R. Brown, July 2003 - M142-63

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2154, Surveyed April/May 2007 - DCSO records Vol. 57 Page(s) 22574

The ¼ sec. cor. of secs. 4 and 9, monumented with an iron post, 2½" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.
from which BTs mkd. by Jelley and Roseberry in 1966-67
A fir, 16" dia., bears N.57°E., 22.8 ft., with a healed blaze.
A fir, 16" dia., bears S.59°E., 25.7 ft., with a healed blaze.