

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6339)

Set Cedar post for 1/4 sec. cor., from which
A Laurel 6" dia., bears N.10°E., 20 lks. dist.
A Fir 20" dia., bears S.68°W., 11 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow, crew - Feb. 6, 1959 - C.S. File 49/47-6

Found - Orig. 20" now 30" R.Fir shows good bark scribing "1/4 S BT", S.68°W., 7.3 ft.
Stump hole that checks bearing and distance for orig. NE. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 3 W
1/4 S33 | S34
1959

New BTs- 8" Cedar bears S.63°E., 23.5 ft. scribed 1/4 S34 CSBT
30" R.Fir bears S.68°W., 8.0 ft. scribed 1/4 S33 CSBT

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14036)

The 1/4 sec. cor., perpetuated and recorded by Byron in 1959, monumented with an iron post, 1" dia., firmly set, extending 6" above ground with 1959 brass cap

from which the remaining original bearing trees
A Fir 27" dia., bears S.68°W., 11 lks. dist., with original bark scribes 1/4 S BT visible. Remarkd by Byron in 1959, blaze now healed.

and a new bearing tree

A Fir 13" dia., bears N.69 3/4°E., 62 lks. dist., mkd. 1/4 S34 BT.

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - 10/2004 - M 145-76

Found - 2 1/2" County Surveyors brass cap dated 1959 with the following accessories;

29" D.Fir bears S.68°W., 7.3' - healed face

13" D.Fir snag bears N.69 3/4°E., 40.9' - open face

New BT - 28" I.Cedar bears S.87°E., 34.8' - blazed, scribed "1/4 S34 BT"