

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6303)

Set post cor. secs. 21, 22, 27 and 28, from which
A Fir 10" dia., bears S.16°E., 25 lks.
A Fir 6" dia., bears N.13°W., 33 lks.
A Fir 36" dia., bears N.5°E., 80 lks.
A Laurel 12" dia., bears S.10°W., 44 lks.

Cor. Fd. and used in GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6341)

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow, crew - Feb. 19, 1959 - C.S. File 49/47-7

Found - Orig. 36" now 44" Fir snag, N.5°E., 52.8 ft., shows good bark scribing.
Orig. 12" now 30" Laurel S.10°W., 29.0 ft., center rotted.
Orig. 10" now 18" Fir, S.16°E., 16.5 ft., shows good scar, I do not open.
Orig. 6" now 18" Fir, N.13°W., 21.8 ft., shows good scar, I do not open.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 3 W
S 21 | S 22
S 28 | S 27
1959

New BTs- 20" R.Fir bears N.39°E., 28.9 ft. scribed S22 T29S R3W CS BT.
6" R.Fir bears S.60°W., 55.2 ft. scribed S28 CS BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16878-79)

The Sec. cor., perpetuated and recorded by Byron in 1959, monumented with an iron post 1¼" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1959 from which the remains of the original bearing trees
A decayed Fir stump, size indeterminate, bears N.5°E., 80 lks. dist., no marks visible.
A Fir 22" dia., bears S.16°E., 25 lks. dist., with healed blaze.
A Laurel 25" dia., bears S.10°W., 44 lks. dist., no marks visible.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A Fir 18" dia., bears N.13°W., 33 lks. dist., with healed blaze.
and bearing trees mkd. by Byron
A Fir stump 20" dia., bears N.36½°E., 44 lks. dist., with scribe marks BT visible on opened blaze.
A Fir 10" dia., bears S.57°W., 84 lks. dist., with healed blaze.
and a new bearing tree
A Fir 12" dia., bears N.76°E., 68 lks. dist., mkd. T29S R3W S22 BT.

From this point, Douglas County, 2nd Order, Horizontal Control Station "DAY", bears N.82°50'E., 82.11 chs. dist., monumented with a brass tablet, firmly set in concrete, flush with ground, with tablet mkd. "DAY 1978".

David Edwards - For: Seneca Jones Timber Co. & Silver Butte Timber Co. - 1/2007 - M 152-14

Found - Brass cap
26" Madrone S.10°W., 29.0 ft.
14" Fir S.57°W., 55.4 ft.
24" Fir N.13°W., 21.8 ft.
New - 7" dia., Fir bears S.39°E., 10.3 ft.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2157, Surveyed March/May 2007 - DCS0 records Vol. 57 Page(s) 22558

The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A decayed fir stump, size indeterminate, bears N.5°E., 52.8 ft., with no marks visible.
A fir, 20" dia., bears S.16°E., 16.5 ft., with a healed blaze
A madrone, 27" dia., bears S.10°W., 29.0 ft., with no marks visible.
A fir, 27" dia., bears N.13°W., 21.8 ft., with no marks visible.
and remains of a BT mkd. by Byron, in 1959
A fir, 16" dia., bears S.57°W., 55.4 ft., with a healed blaze.
and remains of a bearing tree mkd. by Jelley and Rogers
A fir snag, 14" dia., bears N.76°E., 44.9 ft., with no marks visible on a partially healed blaze.
continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing tree mkd. by person(s) unknown
A fir, 8" dia., bears S.41½°E., 10.4 ft., with scribe marks T29S R3W S27 BT visible on an unhealed blaze.
and new bearing tree
A fir, 9" dia. bears N.47°E., 55.9 ft mkd. T29S R3W S22 BT

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2804, surveyed Aug/Sept 2015 - (DCSO records Vol. 58 Page 23423-5 & Plat T29-3 2017-1)

The cor. of secs. 21, 22, 27, & 28, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd from which the remains of the original BTs reported by Skeesick and Browning in 2007
A decayed fir stump, size indeterminate, bears N.5°E., 52.8 ft., with no marks visible.
A fir, 20" dia., bears S.16°E., 16.5 ft. with a healed blaze.
A madrone, 28" dia., bears S.10°W., 29.0 ft., with a hollowed blaze.
A fir 29" dia., bears N.13°W., 21.8 ft., with a healed blaze.
and the remains of a BT mkd. by Byron, in 1959, not reported by Skeesick and Browning
A decayed fir stump, size indeterminate, bears N.36½°E., 29.0 ft., with no marks visible on an open blaze.
and the remains of a BT mkd. by Byron, in 1959, reported by Skeesick and Browning
A sawed fir stump, 17" dia., bears S.57°W., 55.4 ft., with a healed blaze.
and the remains of a BT mkd. by Jelley and Rogers in 1979-80, reported by Skeesick and Browning
A fir snag, 14" dia., bears N.76°E., 44.9 ft., with scribe marks BT visible on a partially healed blaze.
and a BT mkd. by Edwards, in 2007, reported by Skeesick and Browning as person(s) unknown
A fir, 9" dia., bears S.41½°E., 10.4 ft., with a healed blaze.
and a bearing tree mkd. by Skeesick and Browning
A fir 11" dia., bears N.47°E , 55.9 ft., with fragmentary scribe marks visible on a partially healed blaze.