

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6303)

Set ¼ sec. post, from which
A Cedar 10" dia., bears S.30°W., 11 lks.
A Fir 10" dia., bears S.5°E., 14 lks.

Fd. and used in GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6342)

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16879-80)

Point for the ¼ sec. cor. of secs. 21 and 22, determined by the irregular boundary method; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S R 3 W
¼
S 21 | S 22
1980

from which

A Fir 7" dia., bears S.18°E., 25 lks., mkd. ¼ S22 BT.
A Fir 8" dia., bears S.38¼°W., 46 lks., mkd. ¼ S21 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2804, surveyed Aug/Sept 2015 - (DCSO records Vol. 58 Page 23423-5 & Plat T29-3 2017-1)

The ¼ sec. cor. of secs. 21 & 22, monumented with an iron post 2½" dia., firmly set, projecting 3" above ground with brass cap (properly) mkd,

from which the BTs mkd. by Jelley and Rogers in 1979-80

A fir 14" dia., bears S.18°E., 16.5 ft., with a healed blaze.
A fir, 15" dia., bears S.38¼°W., 30.4 ft., with a healed blaze.