

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6303)

Set post cor. secs. 15, 16, 21 and 22, from which
A Fir 36" dia., bears S.75°E., 10 lks.
A Fir 24" dia., bears N.5°W., 56 lks.
A Cedar 10" dia., bears N.80°E., 70 lks.
A Cedar 6" dia., bears S.65°W., 71 lks.

Fd. and used in GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6342)

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - April 11, 1961 - C.S. File 49/47-22

Found - Orig. 10" now 30" Cedar, N.80°E., 46.2 ft., previously opened, shows good reverse scribing.
Stump of orig. SW. BT.
The SE. BT is now a snag, shows old axe blaze.
The orig. NW. BT shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 3 W
S 16 | S 15
S 21 | S 22
1961

New BTs- 18" W.Fir bears N.51°W., 9.0 ft. scribed S16 T29S
R3W CS BT.
12" W.Fir bears N.82°E., 21.6 ft. scribed S15 T29S
R3W CS BT.
17" R.Fir bears S.62°W., 29.7 ft. scribed S21 T29S
R3W CS BT.
19" Pine bears S.46°E., 55.7 ft. scribed S22 T29S
R3W CS BT.

Fd. and used in BLM resurvey by Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Group #857, Surveyed - July/Oct. 1975 - (DCSO records Vol. 38 Page(s) 15615)

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16880)

continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2804, surveyed Aug/Sept 2015 - (DCS0 records Vol. 58 Page 23423-5 & Plat T29-3 2017-1)

The cor. of secs. 15, 16, 21, & 22, monumented with an iron post, 1¼" dia., firmly set, projecting 15 ins. above ground, with brass cap mkd.

from which the remains of the original bearing trees reported by Jelley and Rogers in 1979-80

A cedar, 38" dia., bears N.80°E , 46.2 ft., with a hollowed blaze

A decayed fir snag, 33" dia., bears S.75°E., 11.2 ft., with axe marks visible on a healed blaze. (Record, 6.6 ft.)

A decayed, cedar stump, 26" dia., bears S.65°W., 46.9 ft., with axe marks visible on a healed blaze.

A decayed, fir stump, 46" dia., bears N.2°W., 37.0 ft., with no marks visible.

and BTs mkd. by Byron, in 1961, reported by Jelley and Rogers

A fir, 16" dia bears N.82°E., 21.8 ft., with a healed double blaze

A pine, 36" dia., bears S.46°E., 55.4 ft., with a healed blaze.

A fir 31" dia., bears S.62°W., 29.7 ft., with a healed double blaze.

A fir, 25" dia., bears N.51°W., 9.2 ft., with a healed double blaze.

NAD 1983 (2011)

Latitude 43°02'34.37"N. Longitude 123°03'33.87"W.