

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6304)

-----  
Set ¼ sec. post, from which  
A Fir 30" dia., bears N.45°E., 15 lks.  
A Fir 12" dia., bears S.75°W., 52 lks.

Fd. and used in GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6343)

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - April 11, 1961 - C.S. File 49/47-23

-----  
Found - Orig. 12" R.Fir now 24", S.75°W., 34.3 ft, shows good scar near base, I rescribe this BT "¼ S16 CS BT".

Orig. 30" now 40" R.Fir, N.45°E., 9.9 ft., shows bark scribing and good scar below.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 3 W  
¼ S16|S15  
1961

Fd. and used in BLM resurvey by Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed July/Oct. 1975 Under Group #857, - (DCSO records Vol. 38 Page(s) 15616)

Fd. OK, June 1992 by W. Ruppert - M 115-48  
Fd. OK by R. Brown, May 2000 - M132-40