TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6304-05)

Set ¼ sec. post, from which
A Laurel 18" dia., bears N.50°E., 33 lks.
A Laurel 18" dia., bears N.5°W., 28 lks.

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6343)

Set new post, witness trees standing, viz:
A Laurel 18" dia., bears N.50°E., 33 lks. dist.
A Laurel 18" dia., bears N.5°W., 28 lks. dist.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14038-39)

The ¼ sec. cor., determined at record bearing and distance from the original bearing trees:
A Madrone 22" dia., bears N.50°E., 33 lks. dist., with scribe marks ¼ S visible on opened blaze.
A Madrone 33" dia., bears N.5°W., 28 lks. dist., with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 29 S R 3 W
¼
S 9|S 10
1966
from which a new bearing tree
A Fir 8" dia., bears S.35°E., 31 lks. dist., mkd. ¼ S10 BT.

Fd. OK Oct. 1998 by D. Edwards - M130-67
Fd. BC 8/2018 by N Hibbs, 2018-0027A-B