

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6344)

Set Fir post for cor. to secs. 3, 4, 9 and 10, from which
A Fir 14" dia., bears N.35°E., 50 lks. dist.
A Fir 7" dia., bears S.22°E., 35 lks. dist.
A Fir 7" dia., bears S.35°W., 38 lks. dist.
A Fir 30" dia., bears N.40°W., 11 lks. dist.

Claude Kerr, Logging Engineer - July 1950 - C.S. File 40/262

All BTs destroyed by old burn. Set a Fir stake at intersection of the two old blazed lines and checked West 9.50 chs. to the ridge mentioned in field notes. Distance checked closely. I marked the only close tree for a new BT: 20" Fir N.6°W., 30 ft. dist.

Warren D. Hootman - For: Mr. J.P. Heath - Sept. 21, 1960 (File Jan. 1961) - C.S. File 51/164 and M 20-5

This corner was re-established by Kerr, 1950; said point being witnessed by a Fir and a Cedar as described in Kerr's notes.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Wm. Stoffel, crew - Oct. 1962 - C.S. File 52/126-65

Found no orig. BTs. We do find Kerr's 20" Fir, N.6°W., 30.0 ft., shows good scribing. Also find stake at corner. Set Brass cap alongside stake & mkd: County Surveyors Office

T 29 S R 3 W
S 4 | S 3
S 9 | S 10
1962

Call to creek East of corner checks about 20 ft. short of record.
New BTs- 7" R.Fir S.19°W., 9.0 ft. scribed S9 CS BT.
7" R.Fir S.10°E., 13.9 ft. scribed S10 CS BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13807)

The Sec. Cor., reestablished and recorded by Kerr in 1950, at the intersection of old blazed lines. Subsequently remonumented by Byron in 1962, with an iron post 1" dia., 14" (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

above ground, firmly set, with brass cap mkd. in 1962,
from which a bearing tree mkd. by Kerr
A Fir 23" dia., bears N.6°W., 46 lks. dist. with a
partially healed blaze.
and bearing trees mkd. by Byron
A Fir 8" dia., bears S.11°E., 29 lks. dist., with a
partially healed double blaze.
A Fir 8" dia., bears S.16½°W., 14 lks. dist., with a
partially healed double blaze.
and a new bearing tree
A Fir 8" dia., bears N.89 3/4°E., 71 lks. dist., mkd. T29S
R3W S3 BT.

Fd. and used in BLM Resurvey by James E. Jelley and Lynn
Roseberry Cadastral Surveyors under Group #554 - Surveyed
May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14039)

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor
and Robert H Browning, Survey Tech, Under Group No. 2154,
Surveyed April/May 2007 - DCSO records Vol. 57 Page(s) 22571

The cor. of secs. 3, 4, 9, & 10, monumented with an iron
pipe, 1¼" dia., firmly set, projecting 15" above the ground,
with brass cap (properly) mkd.
from which a bearing tree mkd. by Kerr, in 1950
A fir, 31" dia., bears N.6°W., 30.4 ft., with a healed
blaze.
and bearing trees mkd. by Byron, in 1962
A fir, 13" dia., bears S.11°E., 19.1 ft., with a healed
blaze.
A fir, 14" dia., bears S.16½°W., 9.2 ft., with a healed
blaze.
and the remains of a bearing tree mkd. by Beck in 1964-65
A roothole bears N.89¼°E., 46.9 ft., with fir trunk, 20"
dia., lying alongside, with healed blaze.
and a new bearing tree
A fir, 11" dia. bears N.62°E., 16.9 ft mkd. T29S R3W S3 BT
(NAD 1983 (CORS 96))
Latitude: 43°04'17.09"N Longitude: 123°03'33.11"W

BLM resurvey by George M. Winter, Cadastral Surveyor under
Group No. 2654, surveyed Oct./Nov. 2012 - (DCSO records Vol.
58 Page(s) 23027-8)

The cor. of secs. 3, 4, 9, and 10, monumented with an iron
post, 1¼" dia., firmly set, projecting 15 ins. above ground,
with brass cap (properly) mkd.
continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a BT mkd. by Kerr, in 1950
A fir, 32" dia., bears N.6°W., 30.4 ft., with a healed
blaze.
and bearing trees mkd. by Byron, in 1962
A fir, 13" dia., bears S.11°E., 19.1 ft., with a healed
blaze.
A fir, 14" dia., bears S.16½°W., 9.2 ft., with a healed
blaze.
and a bearing tree mkd. by Skeesick and Browning in 2007
A fir, 11" dia., bears N.62°E., 16.9 ft., with a healed
blaze.
NAD 83 (2011)
Latitude: 43°04'17.09"N. Longitude: 123°03'33.11"W.