

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only, North bdy.

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6326)

-
- Set Fir post for cor. to secs. 3, 4, 33 and 34, from which
- A Laurel 10" dia., bears N.65°E., 19 lks.
 - A Laurel 14" dia., bears S.85°E., 22 lks.
 - A Laurel 20" dia., bears S.45°W., 32 lks.
 - A Laurel 12" dia., bears N.15°W., 14 lks.

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5561)

-
- Cor. secs. 3 and 4, which is a stake, marked as described by the surveyor general. Bearing trees have been destroyed. I destroy markings on this stake referring to secs. 33 and 34, from which
- A Laurel 24" dia., bears S.38°W., 26 lks. dist. mkd. T29S R3W S4 BT.
 - A Fir 8" dia., bears S.40°E., 53 lks. dist. mkd. T29S R3W S3 BT.

Claude Kerr, Logging Engineer - July 1950 - C.S. File 40/262

Found a Laurel that I am certain was the original BT, but the scribe marks are gone. This BT is the Laurel bearing S.85°E. for 22 lks. I reset the corner 3" x 4 ft. Cedar post from this BT, and it checks well for the intersection of the old blazed line. I remarked four new trees:

- I. Cedar 20" bearing S.45°E., 35 lks. mkd. T29S R3W S3 BT.
- Fir 20" bears S.70°W., 36 lks. mkd. S4 BT.
- ~~I. Cedar N.47°E., 34 lks. mkd. T29S R3W S34 BT.~~
- ~~Laurel 12", N.33°W., 39 lks. mkd. T28S R3W S33 BT.~~

(6/12/51 - O & C instructed by Mr. kerr to obliterate markings in secs. 33 and 34) (has been done)

Survey by Warren D. Hootman - For: Mr. J.P. Heath - Sept. 21, 1960 (Filed Jan. 13, 1961) C.S. File 51/164 and M 20-5

I locate the true corner point from a 13" Fir BT, blazed and scribed as per the 1910 notes; this corner is 9.8 ft. North and 15.0 ft. West of corner set by Kerr.

I set a 1" Iron pipe and witness corner as follows:

- 13" Fir, DBH, bears S.41°E., 34.6 ft. mkd. in 1910, scribe marks clearly visible.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only, North bdy.

Alias	Description
Alias	Description
Alias	Description
Alias	Description

14" Laurel DBH, bears N.3°30'W., 11.6 ft. mkd. T28S R3W S33 BT.

The trees marked for the previous corner lay as follows:

20" Cedar bears S.49°E., 38.7 ft. mkd. T29S R3W S3 BT.

20" Fir bears S.28°W., 21.0 ft. mkd. S4 BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13800-01)

The cor. of secs. 3 and 4 only, perpetuated and recorded by Hootman in 1960, with an iron pipe, 1" dia., 8" above ground, from which the SE. bearing tree mkd. by Gibb in 1910:

A Fir 15" dia., bears S.40°E., 53 lks. dist. mkd. 29S R3W S3 BT on an opened blaze.

and a bearing tree mkd. by Hootman:

A Madrone 13" dia., bears N.5°W., 18 lks. dist. mkd. T28S R3W S33 BT on an open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 28 S R 3 W
S 33
S 4 S 3
T 29 S R 3 W
1964

from which a new bearing tree:

A Fir 7" dia., bears S.17°W., 85 lks. dist. mkd. T29S R3W S4 BT.

Reset iron pipe alongside iron post.

From this point, a point established by Claude Kerr, in 1950, bears S.53½°E., 0.25 chs. dist., monumented with a cedar post, 3" sq., 36" above ground, firmly set, mkd. S3 on SE.; and S4 on SW. side, from which trees mkd. by Kerr:

A Cedar 23" dia., bears S.45°E., 36 lks. dist. mkd. T29S R3W S3 BT on an open blaze.

A Fir 23" dia., bears S.56°W., 37½ lks. dist. mkd. with a healed blaze.