

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6340)

-----

Set Laurel post for ¼ sec. cor. from which  
A fir, 15" dia., bears S.24°W., 33 lks.  
A fir, 18" dia., bears N.52°W., 43 lks.

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - 10/2004 - M 145-76

-----

Set - 2½" aluminum cap on 5/8"x30" rebar marked as shown, with the following accessories;  
27" D.Fir bears S.27°W., 21.8' - healed face record S.24°W.  
18" D.Fir stump bears N.50°W., 28.4' - scribe visible record N.52°W.

New BTs -  
15" D.Fir bears S.19°E., 8.1' - blazed, scribed "¼ S34 BT"  
14" D.Fir bears N.7°W., 10.9' - blazed, scribed "¼ S27 BT"  
11" D.Fir bears N.83°W., 24.2' - blazed, scribed "¼ S27 BT"