

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6341)

Set Laurel post for 1/4 sec. cor., from which
A Fir 12" dia., bears S.70°W., 12 lks. dist.
A Fir 14" dia., bears N.40°E., 3 lks. dist.

John H. Markham, Jr. - Wit: Don Perdue - Oct. 23, 1950 -
~~(Record source, not found) (Former Ren. #7)~~ C.S. 40/272-8

Determined by old BT:
A Fir 15" dia., bears N.40°E., 20" dist. I remark 1/4 S
(scribe legible)
A Fir windfall bears S.70°W., 8.0 ft. (Scribe legible)
At corner point, found stone and Set 1" x 30" Iron pipe 6" in
ground, from which
A Laurel 17" dia., bears S.10°E., 22 ft. dist. mkd. 1/4 S
S27 2880 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo
Godfrey; Clete Putnam, crew - April 11, 1961 - C.S. File
49/47-21

Found - Orig. 14" now 18" Fir, down, N.40°E., 2.0 ft., shows
good bark scribing "1/4S".
SE. Laurel BT, now down. This BT recorded by Markham
Also find 1" Iron pipe at corner.

Set brass cap alongside 1" I.P., mkd. County Surveyors Office
T 29 S R 3 W
1/4 S 22
S 27
1961

New BTs- 20" Cedar bears S.68°E., 46.0 ft scribed 1/4 S27 CS BT
9" R.Fir bears N.45 1/2°E., 13.4 ft scribed 1/4 S22 CS BT

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor
and Robert H Browning, Survey Tech, Under Group No. 2157,
Surveyed March/May 2007 - DCSO records Vol. 57 Page(s) 22557

The 1/4 sec. cor. of secs. 22 & 27, perpetuated by Markham, in
1950, remonumented by Byron, in 1961, monumented with an iron
post, 1 1/4" dia., firmly set, projecting 16" above ground, with
brass cap (properly) mkd.
from which the remains of the original bearing trees
A roothole bears N.40°E., 2.0 ft., with decayed fallen fir
trunk, size indeterminate, lying alongside, with no
marks visible. continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, size indeterminate, bears S.70°W., 7.9 ft., no trunk remains.
and remains of a bearing tree mkd. by Markham
A burned madrone root bears S.13°E., 21.4 ft with no marks visible and madrone trunks, 4" dia., growing from it.
and bearing trees mkd. by Byron
A fir, 20" dia., bears N.43¾°E., 13.6 ft., with a healed blaze.
A cedar, 21" dia., bears S.72½°E., 43.0 ft., with a healed blaze.
An iron pipe, 1¼" dia., projects 22" above ground, from the base of the iron post.