

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6342)

Set Fir post for 1/4 sec. cor., from which
A Cedar 22" dia., bears North, 4 lks. dist.
A Laurel 12" dia., bears S.40°W., 21 lks. dist.

Survey by John H. Markham, Jr. - Wit: Geo. Vaughn - Aug. 17 & 25, 1950 - C.S. File 40/272-7

Determined by old BT:
A Cedar 36" dia., bears East, 2.5 ft., scribe legible.
At corner point, Set 1" x 30" I.P., 15" in ground, from which
A Fir 6" dia., bears N.33°W., 18.0 ft. mkd. 1/4 S S15 2880
BT.
A Fir 7" dia., bears S.44°E., 29.0 ft. mkd. 1/4 S S22 2880
BT.
(magnetic var. sec. line 14°30')

BLM resurvey by Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed July/Oct. 1975 Under Group #857, - (DCSO records Vol. 38 Page(s) 15614)

The 1/4 sec. cor., determined from the remains of the original bearing trees:
A Cedar 36" dia., bears North 4 lks. dist., with fragmentary scribe marks visible on open burned blaze.
A Madrone root crown bears S.40°W., 21 lks. dit.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 18" in the ground, with brass cap mkd:
T 29 S R 3 W
1/4 S 15
S 22
1975
from which bearing trees mkd. by Markham in 1950:
A Fir 12" dia., bears N.29°W., 32 lks. dist., with healed blaze.
A Fir 10" dia., bears S.35°E., 39 lks. dist., with healed blaze.

From this point, a local cor. established by Markham in 1950, bears N.45°W., 5 lks. dist., monumented with an iron pipe 1" dia., firmly set, projecting 8" above ground.