

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 440640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13809)

Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line.
Set an iron post 28" long, 2½" dia., 22" in the ground, with brass cap mkd. C¼ S 3
1964

from which

- A Fir 9" dia., bears S.70 3/4°E., 20 lks., mkd. C¼ S3 BT.
- A Fir 13" dia., bears N.7 3/4°W., 56 lks., mkd. C¼ S3 BT.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2654, surveyed Oct./Nov. 2012 - (DCSO records Vol. 58 Page(s) 23032)

The center ¼ sec. cor. of sec. 3, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.
from which bearing trees mkd. by Beck in 1964-65
A fir, 20" dia., bears S.70¾°E., 13.2 ft., with a healed blaze.
A fir, 24" dia., bears N.7¾°W., 37.0 ft., with a healed blaze.