

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 473500

PRIMARY CORNER DESCRIPTION Wit. Cor. for Sec. Cor. 10 & 15 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCS0 records Vol. 15 Page(s) 6304)

Marked a Maple 4" dia., from which
A Fir 18" dia., bears S.15°W., 22 lks.
A Fir 15" dia., bears N.60°W., 21 lks.

Fd. and used in GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCS0 records Vol. 15 Page(s) 6343)

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Dec. 18, 1957 - C.S. File 49/47-1

Found - Orig. 18" Fir now 26" Fir snag, S.15°W., 14.5 ft.
Bark scribed "S 15."
I can find no trace of original NW. BT, nor corner tree.

Set 3/4" Iron rod at corner.

New BTs- 7" R.Fir bears N.30°W., 24.3 ft. scribed W.C. S10 CS BT.
7" R.Fir bears S.36½°W., (dist.?) scribed W.C. S15 CS BT.