

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 477100

PRIMARY CORNER DESCRIPTION C C for Secs. 2 and 3 only, T30-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6941)

At point of intersection, Set a stone 11x10x6 ins., 7" in the ground for closing cor. to secs. 2 and 3, marked C C on S. face, with 2 notches on E. and 4 notches on W. face, from which

A Laurel 14" dia., bears S.40°E., 32 3/4 lks. dist. mkd. T30S R3W S2 BT.

A Fir 32" dia., bears S.30°W., 17½ lks. dist. mkd. T30S R3W S3 BT.

A Fir 36" dia., bears N.15 3/4E., 63½ lks. dist. mkd. T30S R3W C C S2 and 3 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam, crew - July 1960 - C.S. File 49/47-15

Found all original BTs as recorded. The SE. BT shows good scribing. All BTs in good condition. Also find marked Stone at corner.

Set Brass cap at cor. mkd: County Surveyors Office
C C T29S R3W
S 3 | S2 T30S
1960

Fd. OK H. Johnstone, 10/1980 - M86-6

Fd. Ok by Ronald L. Rice 10/2004 - M 145-76

Ron Quimby - 2/2012 - C.S. File 65/76-21

Found - DCSO brass cap, 14" above ground.
30" madrona S.40°E., 21.6 ft. rotted face.
41" D.Fir (snag) N.15¾°E., 41.9 ft. healed face.
A capped 46" D.Fir stump S.30°W., 11.6 ft healed face.

New - 8" D.Fir bears S.66°E., 9.3 ft. scribed CC S2 BT on single blaze.

6" D.Fir bears S.88°W., 5.1 ft. scribed CC S3 BT on single blaze.

Note - Corner is on the E-W boundary of a clear cut unit to the north, approx. 300' south of road just west of the top of an N-S ridge.