

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION C C for Secs. 34 & 35 only, So Bdy

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6319)

Set Fir post for sec. cor. 2,3, 34 and 35, from which
A Laurel 14" dia., bears N.72°E., 30 lks.
A Laurel 12" dia., bears S.85°E., 43 lks.
A Laurel 20" dia., bears S.81°W., 110 lks.
A Fir 24" dia., bears N.38°W., 50 lks.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6939 and 6940-41)

(Page 6939)
The Sec. Cor. for 2, 3, 34 and 35, which cor. is a post, 4" sq., firmly set, marked T29S S35 on NE. face and 2 notches on E. and 4 notches on W. edges, there are other surveyor marks on it but I can not distinguish them, from which
A Laurel 14" dia., bears N.72°E., 30 lks. dist. mkd. T29S R3W S35 BT.
A Laurel 12" dia., bears S.85°E., 43 lks. dist. mkd. T30S R3W S2 BT.
A Laurel 20" dia., bears S.81°W., 110 lks. dist. mkd. T30S R3W S3 BT.
A Fir 24" dia., bears N.35°W., 70 lks. dist. mkd. T29S R3W S34 BT.

The witness tree in sec. 34 does not agree in direction and distance with notes furnished me.

(Page 6940-41)
I remove the post, cor. to secs. 2, 3, 34 and 35 and Set a stone 12x10x6 ins., 8" in the ground, for cor. to secs. 34 and 35, marked with 2 notches on E. and 4 notches on W. edges, from which
A Laurel 14" dia., bears N.72°E., 30 lks. dist. mkd. T29S R3W S35 BT.
A Fir 24" dia., bears N.35°W., 70 lks. dist. mkd. T29S R3W S34 BT.

I destroyed the marks on the witness trees in secs. 2 and 3 in T30S R3W as this is not a cor. to secs. 2 and 3.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey, Clete Putnam, crew - July 1960 - C.S. File 49/47-15

Found - Orig. 24" now 40" Fir N.35°W., 46.2 ft., shows good scar.
(Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION C C for Secs. 34 & 35 only, So Bdy

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. 14" now 20" Laurel N.81°E., 19.8 ft. (Rec. N.72°E.), shows good scribing "S35".
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 3 W
S34|S35
T 30 S
1960
Rescribe now 20" Laurel N.81°E., 20.4 ft. T29S R3W S35 CS BT.

Fd. OK H. Johnstone, 10/1980 - M86-6

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - 10/2004 - M 145-76

Found - 2½" County Surveyors brass cap dated 1960 with the following accessories;
42" D.Fir stump bears N.35°W., 46.2' - healed face
25" madrone bears N.81°E., 20.4' - no marks
New BTs- 14" D.Fir bears N.3°E., 15.7' - blazed, scribed "T29S R3W S35 BT"
9" D.Fir bears N.56°W. 6.7' - blazed, scribed "T29S R3W" S34 BT.

Ron Quimby - 2/2012 - C.S. File 65/76-22

Found - DCS0 brass cap 12" above ground.
42" Fir stump N.35°W., 46.2 ft. healed face.
26" madrona N.81°E., 20.4 ft. no marks.
16" fir N.3°E., 15.7 ft. good scar.
12" fir N.56°W., 6.7 ft. good scar
New - 14" madrona bark scribed S34 BT bears N.10°W., 34.1 ft.
Note - Corner is in SE corner of clear cut unit on south slope approx. 250' south of road.

2