

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6335)

Set Maple post for the ¼ sec. cor., from which
A Fir 48" dia., bears N.42°E., 15 lks. dist.
A Laurel 6" dia., bears N.15°W., 40 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Dale McFarland, crew - Aug. 1961 - C.S. File 49/47-25

Found - Orig. 48" now 50" R.Fir snag, N.42°E., 9.9 ft., shows good bark scribing "BT".
Orig. NW. BT, not found.
Corner falls on right bank of small stream.
I SET WITNESS CORNER 30 ft. North of true corner.
Marked a brass cap "W.C. 30' South to ¼ S27|S26 T29S R3W County Surveyor's Office 1961".
New BTs- 9" R.Fir bears N.37°W., 13.5 ft. scribed W.C. ¼ S27 CS BT.
8" R.Fir bears N.61°E., 30.4 ft. scribed W.C. ¼ S26 CS BT.

Fd. Ok by Ronald L. Rice 10/2004 - M 145-76