

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6335)

-----  
Set an Alder post for cor. to secs. 22, 23, 26 and 27, from which

- A Maple 15" dia., bears N.45°E., 10 lks. dist.
- A Maple 16" dia., bears S.80°E., 27 lks. dist.
- A Maple 22" dia., bears S.35°W., 5 lks. dist.
- A Maple 20" dia., bears N.25°W., 26 lks. dist.

Survey by John H. Markham, Jr. - Wit: Geo. Vaughn - Aug. 17 & 25, 1950 - C.S. File 40/272-3

-----  
As set per govt. field notes. At corner point, found stone marked X. I set a 3/4" x 30" I.P., 12" in ground, from which

- A Maple 23" dia., bears S.57°W., 4.0 ft. mkd. S27 2880 BT
- A Maple 20" dia., bears N.42°E., 6.0 ft. mkd. S23 2880 BT
- A Fir 11" dia., bears S.75°E., 71.0 ft. mkd. S26 2880 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - April 11, 1961 - C.S. File 49/47-21

-----  
Found all BTs and iron pipe as recorded by Markham. SE. BT, now down.

- New BTs- 12" Cedar bears S.64°E., 102.8 ft. scribed S26 T29S R3W CS BT.
- 5" W.Fir bears N.28°E., 25.6 ft. scribed S23 CS BT.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - K. Cheney, crew - Nov. 4, 1976 - C.S. File 59/26-9

-----  
Found - 3/4" I.P. at corner, pipe loose and badly bent. Orig. 15" now 25" Maple bears N.45°E., 6.6 ft. Tree has old blaze. Orig. Maple 22" bearing S.35°W., 3.3 ft. is down and rotted.

- A 12" now 20" Cedar bears S.63°E., 102.8 ft. (Rec. S.64°E.) Tree has partially healed blaze. I open and find scribing "CS BT"

All other bearing trees are gone.

As Iron pipe is badly bent, I replace marker with a 1" x 30" I.P. with brass cap attached for section corner. Cap stamped:  
(Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyor  
T 29 S R 3 W  
S 22 | S 23  
S 27 | S 26  
1976

New BTs- 10" D.Fir bears S.43°E., 62.9 ft. Tree is double blazed and scribed "T29S R3W S27 CS BT"  
No trees available for scribing in NW. quadrant.

Fd. Ok by Ronald L. Rice 10/2004 - M 145-76

BLM Dependent resurvey by Timothy J. Moore & A. Bert Skeesick, Cadastral Surveyors under Group #2033, surveyed Sept. 2002/June 2003 (DCSO rec. Vol. 55 pg(s) 21326-7)

-----

Cor. of secs 22, 23, 26, & 27 perpetuated by Markham in 1950, & further perpetuated by the Douglas Co Surveyors Office, in 1961 & remonumented by the Douglas Co Surveyors Office, in 1976, monumented with an iron post, 1½" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd. from which the remaining original bearing tree

- A maple, 30" dia., bears N.45°E., 6.6 ft., with healed blaze.
- and a BT mkd. by the Douglas County Surveyors Office, in 1976
- A cedar, 30" dia., bears S.65½°E., 103.5 ft., with scribe marks BT visible on a partially healed blaze.
- and bearing trees marked by person(s) unknown
- A fir, 25" dia. bears S.24¼°E., 33.2 ft. with healed blaze
- A fir, 25" dia., bears S.40¼°W., 61.2 ft., with healed double blaze.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2157, Surveyed March/May 2007 - DCSO records Vol. 57 Page(s) 22556

-----

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 1½" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd. from which the remaining original bearing tree

- A maple, 30" dia., bears N.45°E., 6.6 ft., with a healed blaze.
- and BT mkd. by the Douglas County Surveyors Office in 1976
- A cedar, 30" dia., bears S.65½°E., 103.5 ft., with scribe marks BT visible on a partially healed blaze.
- and BTs mkd. by person(s) unknown reported by Moore & Skeesick
- A fir, 25" dia., bears S.24¼°E., 33.2 ft., with a healed blaze.

continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 25" dia., bears S.40¼°W., 61.2 ft., with a healed double blaze.  
(NAD 1983 (CORS))  
Latitude: 43°01'38.41"N.      Longitude: 123°02'26.36"W