

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6336)

Set Hemlock post for the cor. to secs. 14, 15, 22 and 23, from which

- A Maple 8" dia., bears N.42°E., 20 lks. dist.
- A Fir 18" dia., bears S.65°E., 39 lks. dist.
- A Cedar 48" dia., bears S.60°W., 48 lks. dist.
- A Cedar 44" dia., bears N.65°W., 45 lks. dist.

Survey by John H. Markham, Jr. - Wit: Geo. Vaughn - Aug. 17 & 25, 1950 - C.S. File 40/272-6

Determined by old BT:

- A Cedar 55" dia., bears N.65°W., 30.0 ft. scribe legible.
 - A Cedar windfall bears S.65°W., 32.0 ft.
- At corner point, Set 1" x 30" I.P., 18" in ground, from which
- A Maple 14" dia., bears N.39°E., 12.0 ft. mkd. S14 2880 BT
 - An Alder 8" dia., bears S.72°W., 51.0 ft. mkd. S22 T29S R3W 2880 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-93

Found 1" I.P. at corner and all BTs as recorded, except SW. BT, top is broken.

- New BTs- 6" W.Fir bears S.82°W., 57.9 ft. scribed S22 CS BT.
- 6" W.Fir bears S.52°E., 32.4 ft. scribed S23 CS BT.

BLM resurvey by Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed July/Oct. 1975 Under Group #857, -(DCSO records Vol. 38 Page(s) 15610-11)

The Sec. cor., perpetuated and recorded by Markham in 1950, monumented with an iron pipe 1" dia., firmly set, projecting 12" above ground, from which the remains of the original bearing trees:

- A Maple 15" dia., bears N.42°E., 18 lks. dist., with healed blaze. (Rec. 20 lks.)
 - A Fir 32" dia., bears S.65°E., 39 lks. dist., with healed blaze.
 - A root hole bears S.60°W., 48 lks. dist., with a down Cedar alongside, 48" dia., no marks visible.
 - A Cedar 54" dia., bears N.65°W., 45 lks. dist., with scribe marks T29S R3W BT visible on opened blaze.
- and a bearing tree mkd. by Markham:

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An Alder 8" dia., bears S.72°W., 77 lks. dist., with scribe marks S22 T29S R3W 2880 BT visible on bark. and bearing trees not of record:

A Fir snag 8" dia., bears S.52°E., 49 lks. dist. with healed blaze.

A Fir 14" dia., bears S.82°W., 88 lks., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

T 29 S R 3 W
S 15 | S 14
S 22 | S 23
1975

Reset iron pipe alongside iron post.

BLM Dependent resurvey by Timothy J. Moore & A. Bert Skeesick, Cadastral Surveyors under Group #2033, surveyed Sept. 2002/June 2003 (DCSO rec. Vol. 55 pg(s) 21328-9)

The cor. of secs. 14, 15, 22, & 23, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A maple, 21" dia., bears N.50½°E., 11.9 ft., with healed blaze. (Record, N. 42°E.)

A fir snag, 32" dia., bears S.73¾°E., 24.8 ft., with no marks visible. (Record, S.65°E., 25.7 ft.)

A roothole, bears S.60°W., 31.7 ft., with fallen, decayed cedar trunk, size indeterminate, lying alongside, with no marks visible.

A roothole, bears N.65°W., 29.7 ft., with fallen, decayed cedar trunk, 54" dia., lying alongside, with scribe marks S 5 BT visible on opened blaze.

and the remains of a BT mkd. by Markham, reported by Shaner

A roothole, bears S.72°W., 50.8 ft., with fallen, decayed alder trunk, size indeterminate, lying alongside, with no marks visible.

and the remains of BT mkd by person(s) unknown reported by Shaner

A fir, 23" dia., bears S.79¼°W., 58.1 ft., with healed blaze. (Record, S.82°W.)

and new bearing trees

A cedar 17" dia bears S.12°E. 18.3 ft mkd. T29S R3W S23 BT

A fir, 16" dia bears N.41¼°W. 22.1 ft mkd. T29S R3W S15 BT

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description