

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page 6337)

Marked Fir tree 30" dia., for 1/4 sec. cor., from which
A Fir 24" dia., bears S.40°W., 20 lks. dist.
A Cedar 12" dia., bears N.35°E., 30 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Stoffel, crew - Oct. 1962 - C.S. File 52/126-72

Found both orig. BTs and corner tree. We open NE. BT and find good scribing. Also find good bark scribing on West side of corner tree "1/4S". SW. BT, now snag.
Set brass cap 3.0 ft. North of center of corner tree, now 40" Fir, cap mkd: County Surveyors Office 1962 W.C. 3.0 ft. South to 1/4 S15 | S14 T29S R3W.
New BTs- 17" Cedar bears N.71°W., 29.3 ft. scribed W.C. 1/4 S15 CS BT.
10" Cedar bears S.46°E., 12.6 ft. scribed W.C. 1/4 S14 CS BT.

BLM resurvey by Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed July/Oct. 1975 Under Group #857, -(DCSO records Vol. 38 Page(s) 15611-12)

The 1/4 sec. cor., occupied by the original corner tree, a Fir 40" dia., with scribe marks 1/4 S visible on W. blaze, from which the remains of the original bearing trees:

A Cedar stump 20" dia., bears N.35°E., 30 lks. dist., with fragmentary scribe marks visible on decayed blaze.

A Fir snag 26" dia., bears S.51°W., 23 lks. dist., with healed blaze. (Rec. S.40°W., 20 lks.)

from which new bearing trees:

A Cedar 21" dia., S.66°E., 44 lks. dist., mkd. 1/4 S14 BT.

A Fir 8" dia., bears S.34°W., 104 lks. dist. mkd. 1/4 S15 BT

From this point, a local witness cor., established by Byron in 1962, bears North 4 1/2 lks. dist., monumented with an iron post 1 1/4" dia., firmly set, projecting 12" above ground with cap mkd. in 1962, from which bearing trees mkd. by Byron:

A Cedar 12" dia., bears S.46°E., 19 lks. dist., with scribe marks 1/4 S14 WC CS visible on partially healed blaze.

A Cedar 20" dia., bears N.71°W., 44 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

Continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd OK 10/152018 by DCSO C.S. File 67/45-25
NAD 83 N 514034.20 E 4242343.40
 Lat: 43°02'56.0" Long: 123°02'25.6"