

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec Cor for 11 & 14 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6337)

Set Cedar post for the cor. to secs. 11 and 14, from which
A Fir 15" dia., bears N.55°E., 31 lks. dist.
A Fir 24" dia., bears S.35°E., 24 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey, Clete Putnam, crew - Dec. 17, 1957 - C.S. 49/47-1

Found - Orig. 24" now 28" R.Fir snag, S.35°E., 15.8 ft., shows good bark scribing "T29S R3W S14 BT."
Also find orig. 15" now 26" R.Fir N.55°E., 20.5 ft., shows fair bark scribing.
Set 3/4" Iron rod at corner.
New BTs- 10" Cedar bears S.25½°E., 23.1 ft. scribed T29S R3W S14 CS BT.
18" Cedar bears N.10°W., 25.5 ft. scribed T29S R3W S15 CS BT.
Rescribe orig. now 26" R.Fir N.53°E., 21.0 ft., bark scribe "T29S R3W S11 CS BT."

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Wm. Stoffel, crew - Oct. 1962 - C.S. File 52/126-71

Found 3/4" I. rod at corner and all BTs as recorded. SE. BT is in good condition. NW. BT is now stump, shows scribing. NE. BT, now down.
New BT - 14" Fir N.1°W., 14.0 ft. scribed S15 T29S R3W CSBT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13801-02)

The Sec. cor., on the E. bdy. of sec. 15, perpetuated and recorded by Byron in 1957, with an iron rod 3/4" dia., 10" above ground, firmly set, from which the remains of the original bearing trees:
A down Fir 23" dia., bears N.55°E., 31 lks. dist., mkd. S11 BT and remarked T29S R3W S11 CS BT on bark blaze.
A Fir snag 24" dia., bears S.35°E., 25 lks. dist., 24 lks. to face, mkd. S14 T29S R3W T on bark blaze. (Rec. 24 lks.)
and bearing trees mkd. by Byron in 1957
A Cedar stump 17" dia., bears N.12½°W., 39 lks. dist., mkd. T29S R3W S15 CS BT on double blaze.
(Cont. Next Page)

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec Cor for 11 & 14 only (West)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A Cedar 13" dia., bears S.25¼°E., 35 lks. dist., mkd. T29S R3W S14 CS BT on double blaze.

and a bearing tree not of record

A Fir 16" dia., bears N.1½°E., 21 lks. dist., mkd. T29S R3W S11 CS BT on double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

	T	29	S	R	3	W
	S	15		S	11	
				S	14	
				1964		

Reset iron rod alongside iron post.

BLM resurvey by Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed July/Oct. 1975 Under Group #857, -(DCSO records Vol. 38 Page(s) 15613)

The Sec. cor. monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap mkd. in 1964, from which the remains of the original bearing trees

A root hole bears N.55°E., 31 lks. dist., with a down Fir alongside 23" dia., with scribe marks T29S R3W S11 CS BT visible on bark blaze.

A Fir stump 24" dia., bears S.35°E., 25 lks. dist., with fragmentary scribe marks visible on partially decayed blaze.

and bearing trees mkd. by Byron in 1957

A Cedar 16" dia., bears S.25¼°E., 35 lks with healed blaze

A Cedar stump 17" dia., bears N.12½°W., 39 lks., with scribe marks T29S R3W S15 CS BT visible on open blaze.

and a bearing tree mkd. by Byron in 1962

A Fir snag 16" dia., bears N.1½°E., 21 lks. dist., with scribe marks T29S R3W S15 CS BT visible on open blaze.

and a new bearing tree

A Fir 24" dia., bears N.30°E., 131 lks. dist., mkd. T29S R3W S11 BT.

Fd. OK by D. Edwards, Oct. 1998 - M130-67

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2154, Surveyed April/May 2007 - DCSO records Vol. 57 Page(s) 22564

The cor. of secs. 11 & 14 only, monumented with an iron post, 2½" dia., firmly set, projecting 11" above the ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11 & 14 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir snag, size indeterminate, bears S.28½°E., 20.2 ft. with no marks visible. (Record, fir stump, S.35°E., 16.5 ft.)
and the remains of BTs mkd. by Byron, in 1957, reported by Shaner in 1975
A cedar, 29" dia., bears S.25¼°E., 23.1 ft., with a healed double blaze.
A cedar snag, size indeterminate, bears N.12½°W., 25.7 ft., with no marks visible.
and a bearing tree mkd. by Shaner
A fir, 30" dia., bears N.28¼°E., 86.5 ft., with a healed blaze. (Record, N.30°E.)