TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6338)

Set Laurel post for ¼ sec. cor., from which
A Laurel 15" dia., bears N.45°W., 21 lks. dist.
A Laurel 8" dia., bears S.4°W., 43 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13805)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd: T 29 S R 3 W
¼
S 3 S 2
1964
from which
A Fir 7" dia., bears S.55¼°E., 94½ lks. dist., mkd. ¼ S2 BT.
A Fir 9" dia., bears N.51½°W., 5½ lks. dist., mkd. ¼ S3 BT

Fd. OK Oct. 1999 by D. Edwards - M133-43